

DJ45plus Hp TIJ2.5 Inkjet Coder



The DJ45plus has the features that expand the capability of coding and marking, remote control from an external device. It performs versatile functions to apply a great deal of industrial coding and marking applications. Its built-in communication interfaces, to connect to an external device, makes itself ideal for serialization and track-and-trace applications, and be integrated into an automatic system in the industrial 4.0 era.



A turning point that you need an advanced inkjet printer, the DJ45plus, to proceed massive print jobs and external data printing efficiently.

Coding and marking is simple for manufactures if only the manufacturing date and batch code are required on their products. However, as their business is growing, a plenty of printing files with various templates are created to follow the regulations for different customers. It is time-consuming for prework of production lines such as to find and open the right print file from numerous files and change content correctly.

Obviously, it is vital to build an organized system to manage all the required data and printing message files. DJ45plus, a versatile printer with external connectivity ability, offers a solution for industrial coding and marking. It plays a role to quickly execute database printing, print out variable content, and be integrated into an automatic system, being a part of industrial 4.0 era.





· Select right print job from massive files quickly



Database printing from a computer or cloud server



· Print variable content from an external device



Remotely control and monitor print jobs

Integration through industry standard communication protocols



Communication Interface TCP/IP, USB, RS232

With different connection interfaces, DJ45plus can be integrated with your production line and implement external data printing.









Directly print out the external data that is delivered in ASCII text string

Data is sent to printer via external connectivity and printed out.







· Barcode Reader Application

<Take External Source as File Name> by a barcode reader



• The DJ45plus opens the file (.prn) which is named as the scanned barcode. Every message file can be built for a specific template as print need.

<Data via Index> with database by a barcode reader

Item Number	Product Name	Quantity	Unit price
F22351	Mango	60	\$0.35
F22352	Apple	100	\$0.22
F22353	Grape	40	\$0.26
F22354	Orange	120	\$0.15



- The first column < Item Number> of the database is defined as the index column.
- After receiving the scanned data (F22354, for an instance), DJ45plus searches for the matched data from the index column and picks up the required data in the same row to print out.

Connection to PLC through a BCM Box (Binary Code Module)

- BCM Box: 4 ports to connect to PLC. Data is input via binary code, 0000-1111
- Remote control to open files via the PLC. 16 print message files can be appointed in the DJ45plus controller in advance.
- BCM Box is a customized product, please contact Dotjet for further details.



PLC





Methods to send database to DJ45plus

- Transfer a database file into DJ45plus via a USB stick or by Ethernet.
- 2 Distribute individual string of database one by one to printer by Ethernet.
- 3 Fetch database from MySQL by Ethernet

High-speed list prints up to 10 prints per second. Image file name can be included in a database. Please contact Dotjet for further details.



Database file example: Excel (*.csv)

Network Printing

DJ45plus contains a network interface and protocol that allows a host system to connect to it. Multiple communication methods allow users to design print jobs as their needs. Ideal for serialization and track-and-trace applications.

- · Users can send commands to a DJ45plus and receive feedback by protocol.
- <DJ-Link> PC software is developed for protocol communication.



· Being connected with Dotjet CMD system provides solutions to operation errors when an operator selects a print job. Please refer to the CMD brochure or contact Dotjet for the details.



Integrated into a network to work with a third-party system





ERP exports data sheet to the server. Example: a delivery report.



<<<<<<·

6 Printing data is transferred from the sever to track & trace system.





<<<<<<--

- 6 Data is delivered to the server.
- 3 The DJ45plus collects the data/ file of the delivery report from the server.




4 DJ45plus exports all printing history for Track & Trace.

Remote control & monitor: Dotjet Inkjet CMD System

<Dotjet Inkjet CMD System> includes software and hardware parts:

- Centralize the management of the connected inkjet printers and print jobs: create and distribute files, control print jobs and monitor printing status
- Backup printing message files in the CMD server





Controller Operation

1 7" full-color touch screen to operate the controller.

2 Printing messages can be created by the DJ45plus controller and PC software.

3 Multiple languages for the operation interface.

Multiple-language input method to select.





Main Operation Sections

The easy-to learn software design lets a beginner operate Dotjet printers without barriers.

 Printing status display: printing direction, number of prints, etc.







Ink Cartridge



HP TIJ 2.5 technology

- Hot-swapping cartridge: Effortless to replace an ink cartridge without downtime.
- Smartcard technology to store ink cartridge information. The printer controller reads and downloads the parameters automatically to save user's time to set up printing parameters manually.
- · Low-ink LED indicator.
- External low ink alarm.
- · Bulk ink supply system is optional.

Ink types:

- Aqueous ink
- Solvent ink
- UV-curable ink

SPECIFICATIONS

Model	DJ45plus		
Technology	hp TIJ2.5		
Power requirement	AC110-220V, 50/60HZ		
Display	7" Color LCD with LED back light		
Operation temperature	5°C-45°C (41°F-112°F)		
Controller operating system	Linux		
Message Storage	Up to 1,000 messages		
Printhead controlled ability	Two hp TIJ2.5 printheads		
Print line	Multiple depending on character size		
Print height	Up to 12.7 mm		
Print speed	Aqueous ink: max 60m/ min		
	Solvent ink: max 90m/ min		
Max print length	1 meter		
Printing resolution	300 x 300 dpi		
Ink throw distance	6mm is recommended		
LED indicators	Ink low, print on/ off		
Print capability	Alphanumeric, logos, date/time, shift code, serial number, lot/box number,		
	GS1 barcodes/2D code, table, database, multiple languages characters print,		
	and external data.		
User interface	WYSIWYG. Multiple languages available		
	(some may need translation support)		
External data interface	RS232, USB, TCP/IP		
Features	MySQL database, print data collection, protocol control,		
	image in database, remotely control multiple printers by Dotjet CMD software		
Printhead data line	Standard 75cm and 200cm. Longer cable is optioal		
Weight	Controller: 820g (excluding bracket)		
	Printhead: 380g (excluding cartridge and bracket)		
Dimension(L/W/H)	Controller: 205x140x68(mm), 8.1x5.5x2.7(inches)		
	Printhead: 130x115x94(mm), 5.1x4.5x3.7(inches)		
Optional	Encoder, bulk ink supply, external low ink alarm		
	west Mandheling mitheli		







